

Spatio-temporal neural distance fields for conditional generative modeling of the heart

Kristine Sørensen¹, Paula Diez¹, Jan Margeta², Yasmin El Youssef³, Michael Pham³, Jonas Jalili Pedersen³, Tobias Kühl^{3,4}, Ole de Backer³, Klaus Kofoed³, Oscar Camara⁵, and Rasmus Paulsen¹

¹ DTU Compute, Technical University of Denmark, Kongens Lyngby, Denmark

² KardioMe, Research & Development, Nova Dubnica, Slovakia

³ Heart center, Rigshospitalet, Copenhagen, Denmark

⁴ Dep. of Cardiology, Zealand University Hospital, Denmark

⁵ Physense, BCN MedTech, Universitat Pompeu Fabra, Barcelona, Spain
kajul@dtu.dk

1 Supplementary material




Fig. 1. Completion results for all 20 time frames from our method and CHeart on the same two examples as Figure 2 (main paper) showing the chamfer distance CD between the true and predicted surfaces. See also "Normal_our.mp4", "Normal_CHear.mp4", "Abnormal_our.mp4", "Abnormal_CHear.mp4" for videos of the dynamic sequences.




Fig. 2. Volume curves comparing our method to state-of-the-art method (CHearT) on normal atrial motion (left) and abnormal atrial motion (right) for the same samples as Figure 2 in the main paper.




Fig. 3. Completion results showing the average chamfer distance (CD) between the true and completed surfaces evaluated separately for each of the 20 time frames across the test set.